



Traditional systems - Double lock standing seam

DLSS 1.2.1.04 Turned down foot.





## Scale 1/4

## Notes:

Return fold around eaves strip should be left open

- 1. elZinc® cladding
- 2. Membrane
- 3. Structural underlay
- 4. Folded galvanised steel profiles
- 5. elZinc® perforated sheet
- 6. elZinc® retention profile
- 7. Insulation
- 8. elZinc® hung gutter
- 9. Gutter clip
- 10. Gutter bracket
- 11. elZinc® clip
- 12. Substrate

Sistema de Gestión de Calidad Certificado nº 12 100 42 851 TMS The information contained in this document-drawing- has a purely informative function and been elaborated with the intention of assisting building professionals in regard to the installation of elZinc® clading systems. It is the responsible architect, building contractor and installer in any case to ensure the validity of the specific details employed on each project. Asia-elZinc® rejects any responsibility due to direct or indirect damage that may arise from the use of the information contained in this document



elZinc® Tel. +34 985 676 000 Fax. +34 985 692 000 www.elzinc.es

Asturiana de Laminados S.A. Pol. Ind. de Villallana, Parcela 1 33695 Pola de Lena, Asturias, Spain elzinc@aslazinc.com

All dimensions are indicative unless specified on the drawing Sheet thickness may be exaggerated for clarity