



Traditional systems - Double lock standing seam

01

DLSS 1.2.2.03b Pinched seam upstand with saddle capping.





Scale 1/4

All dimensions are indicative unless specified on the drawing Sheet thickness may be exaggerated for clarity

## Notes:

- Used for medium upstands (vented ridge, step, etc.)
- Seams must be more or less perpendicular to upstands (on plan) for this
- Saddle capping makes detail forming easier than in the traditional detail (see DLSS 1.2.2.3).
- 1. elZinc® cladding
- 2. Membrane
- Structural underlay
- Folded galvanised steel profiles
- 5. elZinc® perforated sheet
- 6. elZinc® retention profile
- 7. Insulation
- 8. elZinc® hung gutter
- 9. Gutter clip
- 10. Gutter bracket
- 11. elZinc® clip
- 12. Substrate

Sistema de Gestión de Calidad Certificado nº 12 100 42 851 TMS

The information contained in this document-drawing- has a purely informative function and been elaborated with the intention of assisting building professionals in regard to the installation of elicino® cladding systems. It is the responsability the architect, building contractor and installer in any case to ensure the validity of the specific dealise imployed on each project. Asla-elZino® rejects any responsibility due to direct or indirect damage that may arise from the use of the information contained in this document



elZinc® Tel. +34 985 676 000 Fax. +34 985 692 000

www.elzinc.es

Asturiana de Laminados S.A. Pol. Ind. de Villallana, Parcela 1 33695 Pola de Lena, Asturias, Spain elzinc@aslazinc.com