


Traditional systems - Double lock standing seam

DLSS 4.1.03b Square vented ridge.



Scale 1/5

All dimensions are indicative unless specified on the drawing Sheet thickness may be exaggerated for clarity

Notes:

- Head of seam shown finished according to DLSS 1.2.2.03b.
- Outline structural details are shown for indicative purposes only.
- 1. elZinc® cladding
- 2. Membrane
- 3. Structural underlay
- 4. Folded galvanised steel profiles
- 5. elZinc® perforated sheet
- 6. elZinc® retention profile
- 7. Insulation
- 8. elZinc® hung gutter
- 9. Gutter clip
- 10. Gutter bracket
- 11. elZinc® clip
- 12. Substrate








Traditional systems - Double lock standing seam

DLSS 4.1.03b Square vented ridge.



Scale 1/5

All dimensions are indicative unless specified on the drawing Sheet thickness may be exaggerated for clarity

Notes:

- Head of seam shown finished according to DLSS 1.2.2.03b.
- Outline structural details are shown for indicative purposes only.
- 1. elZinc® cladding
- 2. Membrane
- 3. Structural underlay
- 4. Folded galvanised steel profiles
- 5. elZinc® perforated sheet
- 6. elZinc® retention profile
- 7. Insulation
- 8. elZinc® hung gutter
- 9. Gutter clip
- 10. Gutter bracket
- 11. elZinc® clip
- 12. Substrate





