

<p>1. Unique identification code of the product-type Coils and sheets from Asturiana de Laminados S.A, elZinc Slatee Protect+ (Zn-Cu-Ti) EN 988.</p>																										
<p>2.Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4) All products are marked in accordance with the requirements of EN 988.</p>																										
<p>3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer Self-supporting metal sheets for cladding and cladding of roofs and facades</p>																										
<p>4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5). elZinc Rainbow Asturiana de Laminados S.A Polígono industrial de Villallana parcela 1, 33695 Villallana</p>																										
<p>5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) No applicable</p>																										
<p>6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: AVCP System 3 for fire; AVCP System 4 for the rest of characteristics</p>																										
<p>7. Notified body Applus Laboratories. (Notified Body No. 0370), realizó los ensayos de reacción al fuego de acuerdo al sistema 3 (Informes de ensayo: 17/15241-1812.1 M1, Informes de ensayo: 17/15241-1813.1 M1, Informes de ensayo: 17/15241-1813.1 M2, Informes de ensayo: 17/15241-1812.2 M1) Para el resto de características: No aplicable.</p>																										
<p>8. Activity of the European Technical Assessment Body No applicable</p>																										
<p>9. Declared performance</p> <table border="1"> <thead> <tr> <th>Essential characteristics</th> <th>Performance</th> <th>Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Resistencia para fuerzas concentradas (1,2 kN)</td> <td>PND</td> <td>EN 14782:2006</td> </tr> <tr> <td>Water permeability</td> <td>Cumple</td> <td>EN 14782:2006</td> </tr> <tr> <td>Dimensional change</td> <td>$22 \times 10^{-6} K^{-1}$</td> <td>EN 14782:2006</td> </tr> <tr> <td>Release of dangerous substance</td> <td>The materials in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations</td> <td>EN 14782:2006</td> </tr> <tr> <td>Reaction to fire (for Rainbow finishes)</td> <td>Clase A1 (EN 13501-1 (96/603/EC))</td> <td>EN 14782:2006</td> </tr> <tr> <td>External fire performance</td> <td>Clase B_{ROOF} (EN 13501-5 (2000/553/EC))</td> <td>EN 14782:2006</td> </tr> <tr> <td>Durability</td> <td>Zn (Zn thickness (0,7-1)mm) + 35 µm organic coating)</td> <td>EN 14782:2006</td> </tr> </tbody> </table>			Essential characteristics	Performance	Harmonised technical specification	Resistencia para fuerzas concentradas (1,2 kN)	PND	EN 14782:2006	Water permeability	Cumple	EN 14782:2006	Dimensional change	$22 \times 10^{-6} K^{-1}$	EN 14782:2006	Release of dangerous substance	The materials in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations	EN 14782:2006	Reaction to fire (for Rainbow finishes)	Clase A1 (EN 13501-1 (96/603/EC))	EN 14782:2006	External fire performance	Clase B _{ROOF} (EN 13501-5 (2000/553/EC))	EN 14782:2006	Durability	Zn (Zn thickness (0,7-1)mm) + 35 µm organic coating)	EN 14782:2006
Essential characteristics	Performance	Harmonised technical specification																								
Resistencia para fuerzas concentradas (1,2 kN)	PND	EN 14782:2006																								
Water permeability	Cumple	EN 14782:2006																								
Dimensional change	$22 \times 10^{-6} K^{-1}$	EN 14782:2006																								
Release of dangerous substance	The materials in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations	EN 14782:2006																								
Reaction to fire (for Rainbow finishes)	Clase A1 (EN 13501-1 (96/603/EC))	EN 14782:2006																								
External fire performance	Clase B _{ROOF} (EN 13501-5 (2000/553/EC))	EN 14782:2006																								
Durability	Zn (Zn thickness (0,7-1)mm) + 35 µm organic coating)	EN 14782:2006																								
<p>10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p>																										

Signed for and on behalf of the manufacturer by

Miguel Blázquez Requena, Plant Manager

Villallana, January 24th, 2024