



# Cleaning of elZinc<sup>®</sup> finishes

Brief instructions for cleaning  
elZinc rolled products.

[www.elzinc.es](http://www.elzinc.es)

**elZinc**  
Designing with elZinc<sup>®</sup>



## Index

Construction dust and dry dirt	04
Bird droppings, salt, gypsum, fingerprints and cement	04
Adhesive residue	05
Grease and oil residue	05
Graffiti and paint	06
Summary of cleaning procedures	07

## Brief Instructions

Follow the instructions and always test how you're going to clean on a hidden area first. If you don't achieve a satisfactory result please contact your distributor.

## A word of warning first

An abrasive material such as stainless wool can be used to help remove blemishes as a last resort only on elZinc Natural. For any other elZinc finish, the abrasive products would damage the surface.



## Construction dust and dry dirt

### elZinc material

elZinc Alkimi, elZinc Rainbow and elZinc Advance.

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from the top to the bottom, taking care not to force water into the joints between sheets.

## Bird droppings, salt, gypsum, fingerprints and cement

### elZinc material

elZinc Alkimi, elZinc Rainbow and elZinc Advance.

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from top to bottom, taking care not to force water into the joints between sheets.

#### Step Two: Cleaning agents

Diesel fuel.

#### Step two: Procedure

Apply with a cotton cloth and repeat step number one.



## Adhesive residues

### elZinc material

elZinc Alkimi, elZinc Rainbow and elZinc Advance.

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from the top to the bottom, taking care not to force water into the joints between sheets.

#### Step two: Cleaning agents

Pronto furniture polish (Johnson).

#### Step two: Procedure

Spray and wait a few minutes, gently wipe with a cotton cloth and repeat step number one.

## Grease and oil residue

### elZinc material

elZinc Alkimi, elZinc Rainbow and elZinc Advance.

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from the top to the bottom, taking care not to force water into the joints between sheets.

#### Step two: Cleaning agents

Diesel fuel.

#### Step two: Procedure

Apply with a cotton cloth and repeat step number one.



## Graffiti and paint residues

### elZinc material

elZinc Natural, elZinc Slate, elZinc Rainbow and elZinc Advance

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from the top to the bottom, taking care not to force water into the joints between sheets.

#### Step two: Cleaning agents

Graffiti remover 1500 of brand 3M.

#### Step two: Procedure

Spray and wait a few minutes, gently wipe with a cotton cloth and repeat step number one.

## Graffiti and paint residues

### elZinc material

elZinc Graphite, elZinc Crystal, elZinc Oliva and elZinc Lava.

#### Step one: Cleaning agents

Lukewarm water and neutral detergent.

#### Step one: Procedure

Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove any soap residue from the top to the bottom, taking care not to force water into the joints between sheets.

#### Step two: Cleaning agents

If step one doesn't eliminate the paint residues, it is not possible to eliminate without damaging the surface.



Type of mark	eZinc Material	Step One	Procedure	Step Two	Procedure
<b>Construction dust and dry dirt</b>	eZinc Alkimi,* eZinc Rainbow and eZinc Advance	Lukewarm water and neutral detergent	Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove soap residue from the top to the bottom, taking care not to force water into joints between sheets.	Not Applicable	Not Applicable
<b>Bird droppings, salt, gypsum, fingerprints and cement</b>	eZinc Alkimi,* eZinc Rainbow and eZinc Advance	Lukewarm water and neutral detergent	Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove soap residue from the top to the bottom, taking care not to force water into joints between sheets.	Diesel fuel	Apply with a cotton cloth and repeat step number one
<b>Adhesive residues</b>	eZinc Alkimi,* eZinc Rainbow and eZinc Advance	Lukewarm water and neutral detergent	Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove soap residue from the top to the bottom, taking care not to force water into joints between sheets.	Pronto furniture polish (Johnson)	Spray and wait a few minutes, gently wipe with a cotton cloth and repeat step number one
<b>Grase and oil residue</b>	eZinc Alkimi,* eZinc Rainbow and eZinc Advance	Lukewarm water and neutral detergent	Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove soap residue from the top to the bottom, taking care not to force water into joints between sheets.	Diesel fuel	Apply with a cotton cloth and repeat step number one
<b>Graffiti and paint</b>	eZinc Natural, eZinc Slate, eZinc Rainbow and eZinc Advance	Lukewarm water and neutral detergent	Wipe with a soft sponge or cotton cloth. Rinse thoroughly to remove soap residue from the top to the bottom, taking care not to force water into joints between sheets.	Graffiti remover 1500 of brand 3M	Spray and wait a few minutes, gently wipe with a cotton cloth and repeat step number one
	eZinc Graphite, eZinc Crystal, eZinc Oliva and eZinc Lava			Not possible to eliminate without damaging the surface	Not applicable

\* eZinc Alkimi includes eZinc<sup>®</sup> Natural, eZinc Slate<sup>®</sup>, eZinc Graphite<sup>®</sup>, eZinc Crystal<sup>®</sup>, eZinc Oliva<sup>®</sup> and eZinc Lava<sup>®</sup>.

**FACTORY AND HEAD OFFICE**

ASTURIANA DE LAMINADOS, S.A.  
Pol. Ind. de Villallana, Parcela 1  
33695 Pola de Lena – Spain

**T** (0034) 98 567 60 00 / 98 410 60 00

**F** (0034) 98 549 32 02 / 98 569 20 00

elzinc@aslazinc.com

**[www.elzinc.es](http://www.elzinc.es)**